

PunyInform Game Author's Guide

Written by Fredrik Ramsberg and Hugo Labrande

Contents

1	Introduction	3
2	Testing & Debugging	4
2.1	Use the debug commands	4
2.2	Create a command file	4
2.3	Testers	5
3	Optimizations	6
3.1	Things that save hundreds of bytes	6
3.1.1	Use abbreviations properly	6
3.1.2	Omit unused routines	7
3.1.3	Turn off strict error checking	7
3.2	Things that save dozens of bytes	8
3.2.1	Use string constants	8
3.2.2	Replace a switch with an array	8
3.2.3	Compare a value to multiple values	9
3.2.4	Use Simple Doors	9
3.2.5	Set <code>RUNTIME_ERRORS</code> to 0	9
3.3	Things that save several bytes	9
3.3.1	Avoid conditions in mathematical expressions	9
3.3.2	Compare to zero	10
3.3.3	Use the <code>random()</code> statement	10
3.3.4	[Z3-specific] Use the low dictionary resolution to your advantage	10
3.4	Other optimizations	10
3.4.1	Use Manual Scope	10
3.4.2	Use manual setting of reactive attribute	11
3.4.3	Move arrays to static memory	12
4	Before release	13
4.1	Create an IFID	13
4.2	Set Release and Serial	13
4.3	Check limits	14
4.4	Check articles	14

4.5	Turn off DEBUG	15
4.6	Set RUNTIME_ERRORS	15

Chapter 1

Introduction

This document is intended to provide some guidance as well as various tips and tricks for anyone writing a PunyInform game.

Chapter 2

Testing & Debugging

Here are some advice on finding and fixing problems in your game.

2.1 Use the debug commands

PunyInform has a nifty set of commands to be used when debugging. Read the docs on these commands at

<https://github.com/johanberntsson/PunyInform/wiki/Manual#debugging>

and make sure you try them out and understand how to use them. They can be used to teleport to other locations, moving objects to your inventory, checking what's in scope and more. Whenever you're having trouble getting your code to run in *before*, *after* etc, you can use *Actions* and/or *Routines* to figure out which actions are triggered and which user-supplied routines are executed.

2.2 Create a command file

Consider saving a list of commands needed to play the game from start to finish. When playing on a modern interpreter for a modern OS, you can type *recording on* to start saving all commands to a file, and *recording off* to stop. To read a command file and execute all commands in it, type *replay*.

Having a command file like this makes it easy to check that it's still possible to win the game, whenever you have made changes. You can also save a transcript of the game played with the command file, and then compare a playthrough made at a later date to the original transcript to see what has changed - if you broke something, this should make it fairly easy to spot. On Unix-like OSs you can use *diff* to compare. On Windows you may want to install a specialized program such as WinMerge.

2.3 Testers

Don't think it's enough that you test the game yourself. Good beta-testers are invaluable in the process of producing a good game. They will try things you never thought of, and help you find lots of little things and big things that need to be fixed. You will also notice where they get stuck, so you can decide if you want to provide more hints for the solution to some problem, provide an alternate solution, or somehow make it easier.

Ask testers to provide transcripts of playing sessions so that you can easily see if they interact with the game world as you expect. You can also see opportunities to add or improve responses to non-essential actions.

If you don't have any volunteers for testing, you can ask for help in some forum, such as the one at <https://intfiction.org/> .

And of course, make sure you give credit to your testers, as well as others who have somehow helped out with your game.

Chapter 3

Optimizations

PunyInform leaves you with about 100k bytes to write your game (if you're using the z3 format), but sometimes it's not enough. Maybe your ambitious game "almost fits" in the z3 format; maybe you'd like your grand epic to be playable on a single 1541 disk for the C64; maybe you could fit it all on a 130kb disk for the Atari 8bit. But even if you don't get in a situation where you have to make optimizations, you may want to anyway - a shorter game will play smoother on a machine with little memory, like most 8-bit computers. In any case, we're here to help! This chapter will give you some helpful tips and tricks to make your game smaller. Depending on how much time and energy you can spend, you could save up to an extra 10kb on your game file size!

3.1 Things that save hundreds of bytes

3.1.1 Use abbreviations properly

Abbreviations are fixed strings that get replaced by a 10-bit long code in order to save space in the text. You just need to declare them, and the compiler will apply them whenever possible, if you compile with the `-e` switch. A topic of particular interest is which abbreviations to use.

Infocom used the full 96 abbreviations one can declare in the Z-machine. PunyInform ships with 64 abbreviations, which have been picked based on the text in the library files. This saves some space, but these generic abbreviations will not capture the fact that your protagonist's name, "Eyjafjallaökull", could be declared as abbreviated text. A good set of abbreviations is uniquely tailored to your game. Inform's compiler has a switch, `-u`, that looks at your game's text and finds 64 custom abbreviations; it usually gives better results. To have Inform come up with the best set of abbreviations, compile the game with the `-u` switch, and redirect output to a text file, like this:

```
inform6 +lib mygame.inf -v3u > abbreviations.txt
```

Then open the produced text file and scroll to the bottom. Copy the last all the lines at the end of the file beginning with `Abbreviate`, and paste them at the beginning of your source code file, right after the lines at the top with compiler directives. As an alternative, you can put them in a separate file which you `Include` in your main source code file. Also, make sure you have the line `Constant CUSTOM_ABBREVIATIONS`; in your source, before including `globals.h`, or your new abbreviations won't be used.

Very recently, interest in the algorithmics of the problem have led to the creation of tools to compute even better abbreviations. Matthew Russotto's program and Henrik Åsman's program both aim to compute 96 abbreviations on a ZIL game; their algorithms are efficient and written in C. A slightly less efficient solution in Python, written by Hugo Labrande, can output any number of abbreviations in Inform's expected format. In any case, for each of these, you need to generate the gametext of your game (-r switch), then cut out the abbreviations and the vocabulary table, then feed it to them - although Labrande's script is also compatible with Inform 6's newest gametext format, introduced in version 6.35.

In any case, Inform 6.34 and older does not support more than 64 abbreviations; Inform 6.35 allows you to declare up to 96 (if you don't declare any "low string" - that is, set the compiler switches `MAX_ABBREVS` to 96 and `MAX_DYNAMIC_STRINGS` to 0), which saves even more space. You could expect savings of up to 7kb on a 128kb file!

3.1.2 Omit unused routines

The Inform 6 compiler switch `$OMIT_UNUSED_ROUTINES` is off by default, but can be turned on by putting it in the compilation flags. This frees up memory at no cost, and can save several hundred, maybe even thousands, of bytes! This switch is set at the start of the file `minimal.inf` so if you base your game on that file, you have this covered.

3.1.3 Turn off strict error checking

By default, the Inform compiler adds code to every z5 or z8 game to check for a number of problems in your code at runtime. This is a useful and nice feature, but it makes the game slower and ~10 KB larger, so you probably want to turn it off when targeting 8-bit computers. You do this with `--S`. This is done in the first line in `minimal.inf`.

Just keep in mind that this mechanism exists, and if you get weird errors or crashes you may want to enable it for testing. Note that you'll need to compile as z5 or z8 for it to work.

3.2 Things that save dozens of bytes

3.2.1 Use string constants

If you have a string of over 10 characters repeated somewhere in your code, you could declare that string to be a constant, then point every instance of it to the constant instead. Something like

```
Constant MSG_LOOKS_DANGEROUS = "Going in that direction looks dangerous.";
Constant MSG_HAM " braised ham with mashed potatoes and green beans";
```

```
Object Pub "Pub"
  with
    description [;
      "You're in the pub. Dark doorways lead north and west.
        On the menu today:", (string) MSG_HAM, ".";
    ],
    before [;
      OrderFood:
        "You decide to order the", (string) MSG_HAM,
        ". Yummy, that was delicious!";
    ],
    n_to MSG_LOOKS_DANGEROUS,
    w_to MSG_LOOKS_DANGEROUS,
    s_to Street,
  has light;
```

Depending on the size of the text fragment that's repeated, you could save anywhere from a few bytes to a few hundred bytes. You can also tweak your text so very similar sentences end up being the same ("There is no power on the island" vs "There isn't any electricity on the island"). Using this technique repeatedly can yield savings of a few kilobytes in a long game, at the expense of making your code a bit less readable; just make sure you use explicit constant names.

3.2.2 Replace a switch with an array

If you have a large conditional switch statement for which the consequences are of the same format (they're all a print, or adding something to the same variable, etc), you can turn this into a simple table lookup. Construct an array with the changing values, and use `a->var` to access them. So instead of:

```
switch(i){
  1: print "We are the champions";
  2: print "We will rock you";
```

use this:

```
Array songs "We are the champions" "We will rock you" ...
print (string) songs-->i;
```

This is the opposite of the advice under **2b** in section 45 of the DM4, but that example is for when you want to save on readable memory (which can be no more than 64 KB) by not declaring too many arrays, and you're willing to pay the cost to transform it into a routine.

3.2.3 Compare a value to multiple values

When writing complicated conditions featuring comparing one variable to multiple things (dictionary word, in the case of a `parse_name`, for instance), always group these comparisons using 'or', as follows:

```
if w=='sea' or 'ocean' or 'atlantic' or ....
```

The Z-machine has an opcode to perform such comparisons by groups of three, which the Inform compiler utilizes to generate shorter code.

3.2.4 Use Simple Doors

If you're using more than four doors, you can save space by using `OPTIONAL_SIMPLE_DOORS`. As a bonus, the code gets shorter and more legible. Read more at <https://github.com/johanberntsson/PunyInform/wiki/Manual#doors>.

3.2.5 Set `RUNTIME_ERRORS` to 0

This makes the library less helpful in checking for and reporting errors in your code at runtime, making the game slightly smaller and faster. Keep `RUNTIME_ERRORS` set to 1 or 2 while developing and testing your game, but when you're confident that it's been tested properly and is ready for a public release, set it to 0.

3.3 Things that save several bytes

3.3.1 Avoid conditions in mathematical expressions

Inform has support for evaluating conditions as part of a mathematical expression, as in `return (Lamp has light);` or `danger = (child(elevator) ~= 0)`. However, this requires Inform to generate some complex code, so try not to use it - Write explicit `if` statements instead.

```
return (player == werewolf);
```

will not be as space-efficient as

```
if (player == werewolf) {
    return true;
```

```
} else {  
    return false;  
}
```

3.3.2 Compare to zero

The Z-Machine has an opcode for “test if zero” or “test if non-zero”. If you know that a variable is either true (== 1) or false (== 0), it’s faster and shorter to compare the variable to false than to true. So instead of:

```
if(x == true) print "The squirrel is happy".;
```

use:

```
if(x ~= false) print "The squirrel is happy".;
```

or just:

```
if(x) print "The squirrel is happy".;
```

3.3.3 Use the random() statement

If you want to print a text at random, or return a value at random, don’t forget that the random() statement can take any number of arguments and return one of them with equal probability. No need for a switch or an if to simulate a weighted dice: random(1,2,3,4,6,6) will give you the value you need.

3.3.4 [Z3-specific] Use the low dictionary resolution to your advantage

The z3 format has a resolution of 6 characters; that is, every single word is identified by its first 6 characters. The compiler will replace every word with the suitable dictionary value, which means

```
if(w == 'insect' or 'insects')
```

literally tests the same thing twice. Remove any useless test to save a few bytes every time. This could also help with fitting everything in a “name” property, instead of having to write a “parse_name” routine, which is costly.

3.4 Other optimizations

3.4.1 Use Manual Scope

This is an optimization for speed only. “Scope” means which objects the player, or another actor, can refer to. By default, the PunyInform library will assume that what’s in scope changes whenever a user-supplied routine is called, and this may happen a lot. This causes the library to recalculate the scope quite often,

and this makes the game slower, particularly in situations where a lot of objects are in scope.

If you want to improve on this situation, you can define the constant `OPTIONAL_MANUAL_SCOPE`. This means you take responsibility for telling the library when you have done something that might affect the scope. As a general rule, set `scope_modified` to `true` whenever you use `move` or `remove` or you change any of the attributes `open`, `transparent` or `light`. However, if the object affected is nowhere near the player you don't need to set `scope_modified`. All library routines that move the player or move or modify objects, like `OpenSub()` and `PlayerTo()`, already set `scope_modified` as needed.

Example:

```
Constant OPTIONAL_MANUAL_SCOPE;
```

```
Object Button "button"
  with
    name 'button',
    after [;
      Push:
        move Puppy to location;
        remove self;
        scope_modified = true;
        "A loud click is heard, a puppy comes running into the room,
         and the button sinks into the table, becoming invisible.";
    ],
  has static;
```

3.4.2 Use manual setting of reactive attribute

This is an optimization you can perform to make your game start faster. Unless you have done this, `PunyInform` will look through all your objects when the game starts, and set the `reactive` attribute on all objects that provide `react_before`, `react_after` or `each_turn`. When the game is running, only objects that have this attribute are considered when checking for these properties, for reasons of speed. While letting the library set this attributes automatically works well, it means there's an extra pause as the game starts. For a large game, this could take a few seconds on an 8-bit computer.

These are the steps you need to take to set the attribute manually instead:

1. Define the constant `OPTIONAL_MANUAL_REACTIVE`
2. Compile the game in Debug mode, start it and type the command "DEBUG REACTIVE"
3. For every object which is reported as needing the `reactive` attribute, add the attribute in the source code for that object. Typically, you can skip it for the player object, unless you have added an `each_turn` routine to it.

3.4.3 Move arrays to static memory

If you have arrays whose contents never change, you can place them in static memory, like this:

```
Array my_array static --> 1 2 3 4 5 "String1" "String2";
```

This makes dynamic memory smaller, which means save and restore get faster. Since static memory can also be swapped out, it means gameplay can be smoother in sections of the game where the arrays aren't used.

Chapter 4

Before release

These are some tips you may find helpful when your game can be played from beginning to end, and you feel it's soon ready to be released to the public.

4.1 Create an IFID

There's a standard for identifying text adventures, and it's part of The Treaty of Babel (See <https://babel.ifarchive.org/>). Each game gets an IFID - a unique identifier which can be used to look up data about the game. It's a good idea to include an IFID in your PunyInform game. Somewhere in your source code, you write a section like this:

```
Array UUID_ARRAY string "UUID://XXXXXXXX-XXXX-XXXX-XXXX-XXXXXXXXXXXXX//";  
#Ifdef UUID_ARRAY;#Endif;
```

Instead of all the Xs you put your unique identifier consisting of the characters 0-9 and A-F, which you obtain from <https://www.tads.org/ifidgen/ifidgen> .

The IFID remains the same when you release updated versions of your game. If the game is ported to a new system (say from PunyInform to Twine or Inform 7), it gets a new IFID. Also, if the game is translated to another language (say French), it gets a new IFID as well.

4.2 Set Release and Serial

When you start developing a game, you don't need to set the Release number and Serial number. They will get reasonable defaults. As you release a game, you want to have control over these constants, as this helps identifying which version of the game is available at a certain web site, or which version a certain player is running when they encounter a bug. So, you add something like this near the top of your source code file:

```
Release 1;  
Serial "210131";
```

The recommended way to use the release number is to set it to 1 for the initial release, then increase it by one for each new release you make. The serial number is typically set to the date when the release is made, in the format YYMMDD.

4.3 Check limits

PunyInform has a number of limits which have been set to reasonable values, but some games will need to raise some of these limits. Read about these limits at

<https://github.com/johanberntsson/PunyInform/wiki/Manual#parameters>

The limits which you have to be particularly careful with are:

MAX_TIMERS (default 32): If there is any chance that there could be more than 32 timers or daemons active at the same time, raise this limit. If, on the other hand, you know that you only have say 3 daemons and no timers in your game, you can set **MAX_TIMERS** to 3 to save a bit of dynamic memory. Also search through any extensions you use to check that they're not using timers or daemons before you start lowering this limit.

MAX_SCOPE (default 32): How many objects can be in scope at the same time. Imagine the player picking up all movable objects and placing them in the location with the most static objects. Add any actors, their possessions, the player's body parts if any, etc. **MAX_SCOPE** should be higher than this number of objects. If there's a situation in the game where **MAX_SCOPE** is too low for all objects that should be in scope, some objects will quietly be ignored, meaning some objects can't be referenced and if they have an `each_turn` routine it won't be executed. If the game has been compiled in debug mode, an error message is printed when this happens.

4.4 Check articles

PunyInform has a simple mechanism for printing the indefinite article of an object:

1. If the object has the **proper** attribute, its name is a proper name (like "John") and it has no article.
2. If the object has the **pluralname** attribute, the article is "some".
3. Otherwise, the article is "a".

This works well for most objects. However, sometimes you want to use a different article, such as "an" or "a bunch of" (Of course "a bunch of" isn't an article, strictly speaking, but we can use it as one in PunyInform.). To do this, you add the **article** property to the object, and give it a string or routine as its value.

As object names are more often printed with their definite article, it's easy to miss that some objects may have the wrong indefinite article. Before you release your game, make sure you go through all your objects and check the articles. In particular:

- Check that objects which start with a vowel sound (like airplane, egg and umbrella but not unicorn) have article “an”.
- Check that plural objects either sound fine with the article “some”, or have another article specified. I.e. trousers may have article “a pair of”, bees may have article “a swarm of” etc.

If you want to see the article of an object in action, compile the game in debug mode, *purloin* the object and check your inventory.

4.5 Turn off DEBUG

While the DEBUG mode is invaluable during development, make sure you turn it off when compiling a game for release, or it will allow players to cheat, plus it looks like a rather sloppy release. Note that when the game is compiled in DEBUG mode, a “D” is printed after the library version when the game starts, like “PunyInform v1.9 D”.

4.6 Set RUNTIME_ERRORS

In a production build, when the code has been thoroughly tested, you may want to set RUNTIME_ERRORS to 0. This means the library will only check for a bare minimum of error conditions, and if an error occurs only the error code will be printed, not an explanation of what the error means. This helps make the game file smaller, and the reduced checks also makes it faster. If you still want all error checks, but skip the explanatory error messages, you can set it to 1. This is the default when building without the DEBUG mode. When in DEBUG mode, the default setting is 2, meaning that full error messages are also printed.